



**REMARKS**

- TORQUE SETTING
  - TORQUE ARM PIN NUTS = 150/200 Nm
  - TORQUE ARM CLAMP BOLTS = 90/100 Nm
  - EQUALISER SHAFT NUTS = 290/350 Nm
  - 'U' BOLTS NUTS = 500/540 Nm
  - DROP OUT BOLTS = 75/85 Nm
- FIT FIXED TORQUE ARMS ON KERB SIDE OF TRAILER
- TOLERANCE ON ALL DIMENSIONS ±5mm

**CERTIFICATION UNIT ID:**  
 SINGLE: SARN - 26585  
 TANDEM: SARN - 17051  
 TRIAXLE: SARN - 26584



**FUWA K HITCH AUSTRALIA PTY. LTD.**  
**SUSPENSION - MECHANICAL**  
 1.2m TANDEM, 215mm RIDE HEIGHT  
 CAST HANGERS

Part No.	Description	Qty
1925	SCREW R/ ROD 380&395	1
1927	SCREW R/ROD 465 MM ROD	1
KH600004	END R/ROD RH THREAD	2
KH600005	END R/ROD LH THREAD	2
KH6850003	PIN ASSY R/ROD W/BUSHES	8
KH690007	ROCKER EQUILISER 8"1	2
KH690018B	PIN ASSY EQ ROCKER W/BUS	2
KH690027	SEAT SPRING ULTRA LOW	4
KH690036	HANGER EQUAL 1232MM U/S	2
KH690037	HANGER FRONT & REAR U/SL	4
KH691100/380	RADIUS ROD FIXED 380MM	1
KH691100/470	RADIUS ROD FIXED 470MM	1
KHB12/120/15	BOLT M12X120X1.75 SPRING RET	4
KHB12/15	NUT M12 X 1.75 HEX NYLOC	12
KHB12/45/15	BOLT R/ROD END CLAMP M12	8
LRGBOX	LARGE BOX	1
KH600014	PL SPRING CLAMP	4
KH600037	SPRING ASSY 3 LEAF TAPER	4
KH685004/290	U-BOLT 290MM 3 LEAF	8