



Part No.	Description	Qty
1925	SCREW R/ ROD 380&395	1
1927	SCREW R/ROD 465 MM ROD	2
KH600004	END R/ROD RH THREAD	3
KH600005	END R/ROD LH THREAD	3
KH685003	PIN ASSY R/ROD W/BUSHES	12
KH690007	ROCKER EQUILISER 8"1	4
KH690018B	PIN ASSY EQ ROCKER W/BUS	4
KH690027	SEAT SPRING ULTRA LOW	6
KH690036	HANGER EQUAL 1232MM U/S	4
KH690037	HANGER FRONT & REAR U/SL	4
KH691100/380	RADIUS ROD FIXED 380MM	1
KH691100/470	RADIUS ROD FIXED 470MM	2
KHB12/120/15	BOLT M12X120X1.75 SPRING RET	8
KHB12/15	NUT M12 X 1.75 HEX NYLOC	20
KHB12/45/15	BOLT R/ROD END CLAMP M12	12
LRGBOX	LARGE BOX	1
KH600014	PL SPRING CLAMP	6
KH600037	SPRING ASSY 3 LEAF TAPER	6
KH685004/290	U-BOLT 290MM 3 LEAF	12

FUWA K HITCH AUSTRALIA PTY. LTD.

SUSPENSION - MECHANICAL
2.4m TRI-AXLE, 218mm RIDE HEIGHT
CAST HANGERS

DRG / PART No REV
KHU3B3 A

DATE 06.03.2007
CHECKED
SCALE 1:10 SHEET No. 1 OF 1

CERTIFICATION UNIT ID:
SINGLE: SARN - 26585
TANDEM: SARN - 17051
TRIAXLE: SARN - 26584

REMARKS

- TORQUE SETTING
 - TORQUE ARM PIN NUTS = 150/200 Nm
 - TORQUE ARM CLAMP BOLTS = 90/100 Nm
 - EQUALISER SHAFT NUTS = 290/350 Nm
 - 'U' BOLTS NUTS = 500/540 Nm
 - DROP OUT BOLTS = 75/85 Nm
- FIT FIXED TORQUE ARMS ON KERB SIDE OF TRAILER
- TOLERANCE ON ALL DIMENSIONS ±5mm

DO NOT SCALE

DIMENSIONS IN MILLIMETRES

THIS DRAWING, AND ALL INFORMATION ON THIS DRAWING, IS THE PROPERTY OF FUWA K HITCH AUSTRALIA PTY. LTD. AND MAY NOT BE COPIED IN ANY WAY OR FORM WITHOUT THE WRITTEN CONSENT OF FUWA K HITCH AUSTRALIA PTY LTD.

