



K HITCH (AUSTRALIA) PTY LTD  
PERTH - SYDNEY - BRISBANE - BROKEN HILL

DEMOUNTABLE (FLANGED) KING PINS



PART No.	SAP	DESCRIPTION	D RATING	KG
<b>DEMOUNTABLE KINGPIN ASSEMBLIES includes pin, plate &amp; bolts</b>				
KPBA50/**		50mm King Pin Assembly	240kN	15.45
KPBA75/**		75mm King Pin Assembly	240kN	17.45
KPBA90/**		90mm King Pin Assembly	240kN	17.80
** Equals skid plate thickness				
<b>DEMOUNTABLE KING PIN DROP FORGED with 8 bolt holes D RATED</b>				
KPB50	562	50mm Flange Kingpin	240kN	6.25
KPB75	563	75mm Flange Kingpin	240kN	8.25
KPB90	564	90mm Flange Kingpin	240kN	8.60
<b>RETENTION PLATES</b>				
KPF08	583	08mm retention plate		8.60
KPF10	579	10mm retention plate		8.60
KPF12	580	12mm retention plate		8.60
KPF16	581	16mm retention plate		8.60
KPF20	582	20mm retention plate		8.60
KPF/HD	374	16mm H/D retention plate 20mm bolt		16.25
<b>BOLT KITS</b>				
KPB14	561	HT bolts M14x38mm Grade 10.9 (8 per set)		0.60
KH032	1351	HT bolts M20x50mm Grade 10.9 (singles)		0.18
<b>INDUCTION HARDENED DEMOUNTABLE KING PINS</b>				
KPB75IH	358	75mm Induction Hardened Pin	240kN	8.25
KPB90IH	359	90mm Induction Hardened Pin	240kN	8.60
<b>HEAVY DUTY KING PINS</b>				
KPB90H/D	597	90mm Heavy Duty King Pin Induction hardened	240kN	13.60
		with grease channel uses 20mm bolts		