

K HITCH FABRICATED SUSPENSION STOCK CODE CONFIGURATOR

EXPLANATION OF K HITCH FABRICATED SUSPENSION CODE

Suspension Model KH68 = Fabricated	$\underline{KH68 O 2 B 8} - \underbrace{2 U}_{1} - \underbrace{S F}_{1}$
Slung StyleO= Overslung	
No. of Axles1= Single2= Tandem3= Tri4= Quad	
Axle Spread A = N/A (Single Axle) B = 1232 mm (8.1') C = 1384 mm (9.1') D = 1538 mm (10.1')	
Amount of Spring Pack Leaves 3 = 3 leaves (75 mm x 22 mm) 8 = 8 leaves (75 mm x 13 mm) 9 = 9 leaves (75 mm x 13 mm) 13 = 13 leaves (75 mm x 10 mm)	
Additional Options 2 = 2" axle seat 3 = 3" axle seat U = Urethane bushes M = Mullins bushes O = Offset rocker/hanger (Leave blank if no options required)	
(Leave blank if no options required) *Contact FKH for additional options. Packer Thickness S = 25mm	
Hanger Flange F = Flange	



FUWA FABRICATED SUSPENSION STOCK CODE CONFIGURATOR

EXPLANATION OF FUWA FABRICATED SUSPENSION CODE

